California High-Speed Train Project



Agreement No.: HSR 11-16 Standard Drawings

Revision No.	Date	Description
0	01 Mar 12	Initial Release, R0
1	12 July 13	EXECUTION VERSION

DRAWING DRAWING NO.

SD

SD-CD-002 DITCH DETAILS

SD-CD-003 STORM DRAIN HOLES

| SD-CD-004 | RETAINING WALL DRAINAGE DETAILS

/24/2013 9	
7/24	
Mincio	
Μ̈́	R

						DESIGNED BY R. MINCIO
						DRAWN BY V. HUANTE
						CHECKED BY H. NGUYEN
						IN CHARGE
Α	05/31/13				EXECUTION VERSION	J. CHIRCO
REV	DATE	BY	СНК	APP	DESCRIPTION	07/12/2013

DRAINAGE

DRAWING TITLE SD-CD-001 TRACK DRAIN/UNDERDRAIN, CLEANOUT AND RISER DETAILS

PARSONS BRINCKERHOFF



CALIFORNIA HIGH-SPEED TRAIN PROJECT

STANDARD DRAWINGS CONTRACT PACKAGE 1 SHEET INDEX

DRAWING		X-2	СР
SCALE	NO	SCA	LE

SHEET NO.

SIERRA SUBDIVISION


DRAINAGE AGGREGATE

PERFORATED PVC

45° WYE-


ONE-SACK CEMENT — SLURRY UNDER AND AROUND FITTINGS NOTES: 1. RISER MA

1. RISER MAY BE ANGLED AT 90 DEGREES DUE TO SPACE CONSIDERATIONS.



TERMINAL RISER DETAIL

SCALE: 1"=1'-0"





FINISHED GRADE-COVERAGE

PVC PIPE (TYP)-

INTERMEDIATE RISER/CLEANOUT

SCALE: 1"=1'-0"

-1/2" GALVANIZED BOLT AND NUT WITH FLAT HEAD AND LOCK WASHERS

-POSITIVE JOINT COUPLER (TYP)

-RISER @ 45° (SEE NOTE 1)

-PERFORATED PVC

PROVIDE 6" SECTION OF SOLID PIPE AT START OF PIPE RUNS

> PARSONS BRINCKERHOFF




SCALE: 8"=1'-0"


CALIFORNIA HIGH-SPEED TRAIN PROJECT DRAINAGE STANDARD

TRACK DRAIN/UNDERDRAIN CLEANOUT AND RISER DETAILS


CONTR	ACT 140	, <u>,</u>
DRAWIN	IG NO.	
	SD-	CD-001
SCALE		
	AS	SHOWN
CHEET	NO	




TYPE A (TRAPEZOID) DITCH



TYPE B ("V") DITCH



TYPE C (TRAPEZOID) DITCH





DITCH DETAILS NO SCALE

K. SISTLA DRAWN BY HECKED BY A. ARTAHI CHARGE A 05/31/13 EXECUTION VERSION DATE BY CHK APP DESCRIPTION 07/12/2013

UNLINED DITCH LINED DITCH TOP OF DITCH FLOW * O" FOR FLOW IN REVERSE DIRECTION -BEND FABRIC INTO WALL SEE TYPE A DITCH (TYP) PROVIDE CUT-OFF WALL AT TRANSITION TO UNLINED DITCH

SECTION








NOTES:

- 1. DITCH LINING SHALL BE CONCRETE OR SHOTCRETE.
- 2. DITCH SHALL CONFORM TO THE FOLLOWING MINIMUM DIMENSIONS:
- D = DEPTH OF DITCH, 1 FOOT MINIMUM S = SLOPE OF DITCH, SIDES, 2:1 MAX FOR CONCRETE LINED CHANNEL, 3:1 MAX FOR GRASS LINED CHANNEL W = WIDTH OF BOTTOM OF DITCH, 4 FEET MINIMUM
- 3. TYPE A AND B DITCHES SHALL HAVE A CONTRACTION JOINT EVERY 10 FEET, AND AN EXPANSION JOINT EVERY
- 4. OPEN CHANNEL CLOSURE SHALL BE REQUIRED AT EACH LOCATION WHERE AN OPEN CHANNEL PASSES UNDER AUTHORITY'S RIGHT-OF-WAY.



OPEN CHANNEL CLOSURE DETAIL

NO SCALE

(SEE NOTE 4)




CALIFORNIA HIGH-SPEED TRAIN PROJECT DRAINAGE STANDARD

DITCH DETAILS

CONTIN		•
DRAWIN		CD-002
SCALE		
	NO	SCALE

SHEET NO.



DATE

BY CHK APP

DESIGNED BY K. SISTLA DRAWN BY CHECKED BY A. ABTAHI N CHARGE J. CHIRCO A 05/31/13 EXECUTION VERSION


DESCRIPTION

PARSONS BRINCKERHOFF




NOTES:

1. RETAINING WALL STRUCTURE IS SCHEMATIC AND DOES NOT REPRESENT DESIGN.



RETAINING WALL DRAINAGE

07/12/2013



TYPICAL GUTTER DETAIL

CALIFORNIA HIGH-SPEED TRAIN PROJECT DRAINAGE STANDARD

RETAINING WALL DRAINAGE DETAILS

CONTR	ACT NO.	•
DRAWIN		CD-004
SCALE	NO	SCALE
SHEET	NO.	